

# Phoenix S25



## BRIGHTNESS

2500 Boost  
2100 Standard  
1900 Eco

## DIAGONAL IMAGE SIZE

22" - 260" Inches

## ASPECT RATIO

4:3 Compatible 16:9

## RESOLUTION

800 x 600 SVGA True  
1400 x 1050 SXGA+ Compressed

## DISPLAY TYPE

0.55" x 1, 12° DDR DLP

## CONTRAST RATIO

2000 :1

## LAMP

200 watt OSRAM VIP

## LAMP LIFE

2000 Boost  
3000 Standard  
4000 Eco



## OPTIONAL ACCESSORIES:

Extended warranty  
Mac Adaptor/DVI Adaptor Cable: Audio/VGA/Component/Composite Video  
Universal Ceiling Mount, Suspension Pole  
Round Flush kit  
Spare lamp module

## SHIPS WITH:

Laser Remote Control  
CD ROM Power Cord  
USB Mouse  
S-Video Cable, DVI/VGA 15 pin Computer Cable  
Users Guide, Lens Cap, Soft Carry Case

## PROJECTION LENS

Manual Zoom/Focus

## PROJECTOR CONTROLS

RS232

## THROW DISTANCE

3.2' - 32' Feet  
1 - 10 Meters

USB

12V Trigger

## THROW RATIO

1.89~2.18 ( x screen width)

## INPUTS

VGA  
Composite  
S-Video  
Audio (Mini jack)

## OUTPUTS

Audio (Mini jack)  
VGA (Out)

## COMPATIBILITY

VGA,SVGA,XGA,SXGA, Mac

## KEYSTONE

+/- 15°

## VIDEO COMPATIBILITY

NTSC/NTSC 4.43, PAL  
B/G/H/I/M/N 60, SECAM  
EDTV / SDTV / HDTV  
480i/p / 720p / 1080i

## AUDIO

3w Mono Speaker

## DIMENSIONS

12" x 9.6" x 3.4" Inches  
300mm x 244mm x 88mm

## WEIGHT

7.3 Lbs/3.3 Kg

## DECIBEL RATING

36dB (boost)/33dB (standard)/31dB (eco)

## WARRANTY

3 year parts & labor / 90 day lamp

## FCC CERTIFICATION

FCC-B,UL,C-UL,CD/TUV.CB,CCC

## H-REFRESH RATE

Horizontal—15-90 kHz

## V-REFRESH RATE

Vertical—50-85 kHz

## POWER SUPPLY

AC input 110~240  
Voltage (auto ranging)

## PWR. CONSUMPTION

290W (boost)  
255W (standard)  
230W (eco)

**BOXLIGHT**<sup>®</sup>  
CORPORATION

19462 Powder Hill Place, Suite 101  
Poulsbo, WA 98370

[www.boxlight.com](http://www.boxlight.com)  
Direct 800.762.5757  
International 360.779.7901