

LPX150 | XGA



The LPX 150 can be used during trainings and presentations or as a component of a home cinema. With a brightness level of 1500 ANSI, it perfectly suits small and medium rooms. The LPX 150 can display image in a resolution of 1024 x 768 (XGA) or 1280 x 1024 (SXGA) with a contrast ratio of 400:1. The projector is equipped with a 150 W high quality mercury lamp. The LPX 150 is equipped with D-Sub, Video and S-Video connectors. If the LPX 150 is to be used as a component of a home cinema, functions such as a freeze mode, a 16:9 image format and a PIP (Picture in Picture) will surely come in handy.

Technical data	
Diagonal	40" - 200" (distance of projection 1.33 – 8.34m)
Luminosity	1,500 ANSI lumens
Contrast ratio	400 : 1 typical
Display colour	16.7 Million
Horizontal sync	15 - 80 KHz
Vertical sync	43 - 85 Hz
Maximum resolution	1.3 megapixels (1280 x 1024 / 60 Hz)
Native resolution	0.8 megapixels (1024 x 768 / 85 Hz)
Resolutions	1280 x 1024 / 43, 60, 75 Hz 1152 x 900 / 66, 76 Hz 1024 x 768 / 60, 70, 75, 85 Hz 800 x 600 / 56, 60, 72, 75, 85 Hz 720 x 400 / 85 Hz 640 x 480 / 60, 67, 72, 85 Hz 640 x 350 / 85 Hz 1600 x 1200 / 48 Hz 1280 x 960 / 60, 75 Hz 1152 x 864 / 70, 75, 85 Hz 832 x 624 / 74 Hz 720 x 480 / 70 Hz 720 x 350 / 70 Hz 640 x 400 / 85 Hz
Input connector	D-Sub mini 15 pin, Video, S-Video
Syncronisation	Composite-, Separate, NTSC, PAL, SECAM
Speaker	2 W (mono)
Audio-signal-input	Mono mini jack , Ø 3,5 mm
Focus	manual focus
Zoom	manual zoom; 1.23
Source of light	150 W high-pressure mercury lamp
Noise	max. 35 dB
Controls	OSD menu in 8 languages (D, GB, F, RU, JP, ES, I, Ch)
User controls	uto-Setup, brightness, contrast, phase, clock, horizontal and vertical position, colour temperature (R, G and B controlled independently), vertical trapezoid distortion, zoom, horizontal and vertical image offset, reset, audio signal (volume, bass/treble, mute)
Apple - Mac	All iiyama projectors are compatible with Apple-Macintosh computers.
Warranty	3 years with free transport provided (with the exception of lighting elements)
Safety	TÜV-GS, CE, UL, FCC-B
Power supply	AC 90 – 264V, 50 / 60 Hz
Power usage	max. 210 W
Dimensions w x h x d	233 x 93 x 297 mm
Weight	3.1 kg

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.