

Optoma EP706S



SVGA
DLP



- (TI)DLP® 0.55" 12°
- SVGA DMD
- 5
- 2000 ANSI
- 2000:1
- 3:2, 2:2
- HDTV 720p/1080i 가
- (RGBCYM)
- RGB
- (가)
- / 가
- ()
- RS232
- ID
- 10

EP706	
	TI DLP® / 0.55" SVGA DDR 12° DMD
	: SVGA (800x600), 1280x1024 PC 60Hz
	2000 ANSI
	2000 : 1
	16.7
	F# 2.7 – 3.0 @2.4m, f = 21.83 ~ 23.81 mm 1.10
()	30.7 ~305
(/)	1.93~2.13
	1.5 ~ 12
	± 16° ()
	4:3, 16:9
	: 31.5~68.7kHz, : 56~85Hz
	SXGA, XGA, SVGA, VGA, IBM PC, Apple Macintosh, iMac 가
RGB	HDTV (480i/p, 576i/p, 720p, 1080i), Full NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM
/	VGA (YPbPr/YCbCr, VGA, SCART) x1, mini DIN S-Video x1, RS232 x1, IR () x1
	85 %
	180
	3000
	AC 100~240V 50/60Hz
	2.0 kg / 4.4lbs
	27 dB
(W x D x H)	23cm x 21cm x 9.5cm



Optoma Corporation

5F, No.108, Minchiuan Road
Shindian City, Taipei, Taiwan 231, R.O.C
Tel: +886 2 2218 2360 Fax: +886 2 2218 2313
<http://www.korea.optoma.com>
(Specifications subject to change without notice)