



PLC-XF46E

High Brightness LCD projector



- ◆ 12,000 ANSI Lumens
- ◆ XGA Resolution
- ◆ 1000:1 Contrast Ratio
- ◆ Unique 4 Lamp System
- ◆ Long Life Optical Components
- ◆ Motorised Zoom/ Focus/ Lens Shift
- ◆ New High Quality Video Image Processing System
- ◆ 8 Optional Input Boards including Network Board and SDI Board.
- ◆ 11 Optional Lenses with 'One Touch' Change System
- ◆ Only 37.0 Kg (without lens)

Model name	PLC-XF46E
Panels	1.8 inch TFT p-Si x 3
No. of pixels	3,147,264 (1024x768 dots)
Projection lamp	300W x 4 (UHP)
Brightness	12,000 ANSI lumens
Contrast	1000:1
Uniformity	90% (corner to centre)
Up-down ratio/keystone correction	Lens shift 10:0~1:1(U/D), Digital keystone U/D+/- 30°
Projection lens	Not supplied as standard
Optional lenses	LNS-S02z/S03, LNS-M01z, LNS-W01z /W02z /W03 /W04, LNS-T01z/T02/T03.
Terminal	Detachable - DVI-I - 5-BNC/ (RGBHV/Y,Pb/ Cb,Pr/Cb) - BNC x2 (Video / Y,C) plus S-Video (Mini DIN4)
Audio Out	RCA (L/R)
Communication Terminal	RS232C In / Out (DSub9 x2),
Computer compatibility	UXGA/SXGA/WXGA/XGA/SVGA/VGA/MAC
Colour systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Scanning frequency	H/V sync -120kHz~ 120Hz, Dot clock 230 MHz
Voltage	200-240V AC
Dimensions (W x H x D)	581 x 252 x 783 mm
Weight	37.0 kg